4

RECYCLED PAPER RECYCABLE

. )



# (12) United States Patent

Gradon et al.

(10) Patent No.:

US 6,349,722 B1

(45) Date of Patent:

Feb. 26, 2002

(54)	RESPIRA	TORY HUMIDIFICATION SYSTEM
(75)	Inventors:	Lewis George Gradon; Stephen William McPhee; Paul John Seakins; Peter John Leonard, all of Auckland (NZ)
(73)	Assignee:	Fisher & Paykel Limited, Auckland (NZ)
(*)	Notice:	Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.
(21)	Appl. No.:	09/097,832
(22)	Filed:	Jun. 16, 1998
(30)	Forei	gn Application Priority Data
Jun. Apr.	17, 1997 27, 1998	(NZ)
(51)	Int. Cl. <sup>7</sup>	A61M 15/00; A61M 16/00; H05B 3/00
(52)	U.S. Cl	
(58)	128. 16	earch
(56)		References Cited

## U.S. PATENT DOCUMENTS

2,084,514 A	•	6/1937	Tuttle et al 201/142
3,903,883 A	•		Pecina et al 261/142
4,038,980 A	*	8/1977	Fodor 128/203.17
4,098,853 A	٠	7/1978	Brown et al 261/122
4,201,204 A	٠	5/1980	Rinne et al 128/203.27
4,220,460 A	*	9/1980	Partus 65/3
4,276,243 A	*	6/1981	Partus 261/128
4,393,013 A	•	7/1983	McMenamin 261/64
4,436,674 A	*	3/1984	McMenamin 261/64
4,589,409 A	٠	5/1986	Chatburn et al 128/203.26

4,618,462 A	* 10/	1986	Fisher 261/130
4,621,632 A	* 11/	1986	Bartels et al 128/203.27
4,682,010 A	* 7/	1987	Drapeau et al 219/381
4,705,936 A	* 11/	1987	Fowler 219/295
4,708,831 A	* 11/	1987	Elsworth et al 261/130
4,921,642 A	* 5/	1990	LaTorraca 261/142
5,031,612 A	* 7/	1991	Clementi 128/204.14
5,097,424 A	* 3/	1992	Ginevri et al 364/510
5,163,423 A	* 11/	1992	Suzuki 128/203.26
5,249,740 A	* 10/	1993	Serra Tosio et al 236/44 A
5,331,995 A	+ 7/	1994	Westfall et al 137/8
5,349,946 A	* 9/	1994	McComb 128/203.17
5,537,996 A	* 7/	1996	McPhee 128/204.17
5,558,084 A	9/	1996	Daniell et al.
5,640,951 A	• 6/	1997	Huddart et al 128/204.17
5,938,984 A	<b>*</b> 8/	1999	Jung 261/130
6,050,260 A	* 4/	2000	Daniell et al 128/204.22
6,095,505 A	+ 8/	2000	Miller 261/130

#### \* cited by examiner

Primary Examiner—John G. Weiss Assistant Examiner—Joseph F. Weiss, Jr. (74) Attorney, Agent, or Firm—Trexler, Bushnell, Giangiori, Blackstone & Marr, LTD

### (57) ABSTRACT

A flow probe for use in a humidification system is disclosed. The flow probe is adapted to be positioned in a humidified gases flow (for example oxygen or anaesthetic gases) such as that which is provided to a patient in a hospital environment. The flow probe is designed to provide both temperature and flow rate sensing of the gases flow by incorporating two sensors (preferably thermistors) and the shape and alignment of the probe enables accurate readings by reducing the occurrence of condensation on the sensors. A number of possible applications are disclosed wherein the flow sensor is, included in humidification control systems which provide a patient with a desired humidity level or simplify the amount of user input required or wherein the flow sensor provides a controller with flow information which may then be used to determine certain, possibly dangerous, conditions (such as incorrect flow sensor placement, breathing circuit disconnected, no water in the humidification chamber or humidity out of required limits).

#### 27 Claims, 6 Drawing Sheets

